



## Substrates and preparation

Suitability	Wood and all of the most popular materials, including metals and plastics.
Condition	Load-bearing, clean, grease-free, dry.
Preparation	Mask the edges of the joints with adhesive tape.

## Processing

Inject sealant into the joint using the sealant gun. Smooth within 10 minutes with moistened FUGENGLÄTTER (with clear water). Remove adhesive tape and smooth the edges of the joint.

## Product data

Consumption	approx. 25 ml/m with a 5 x 5 mm joint.
Coverage (310 ml)	approx. 12 m with a 5 x 5 mm joint.
Processing temperature	5-30 °C.
Joint width	5-30 mm.
Skin formation time	10-15 minutes
Can be sanded/treated	after 3 days.
Long-term elasticity:	10 %.
Ingredients	Artificial resin dispersion, modified natural resins, calcitic fillers, pigments, anti-frothing agents, thickening agents
Ecology	Solvent-free. Very low emissions <sup>PLUS</sup> (EMICODE EC 1 <sup>PLUS</sup> ).
Colours	maple, antique white, beech, oak, silver-grey oak, cherry, midnight brown, walnut.
Package size	310 ml.
Storage life	Usable in original packaging until at least: See printing on package. Store in a frost-free location. All times based on 15-20 °C and 65 % rel. humidity. Higher temperatures reduce hardening time, lower temperatures increase hardening time.

## Please note

Low temperatures and high humidity increase skin formation time. Unsuitable for effect of standing water. Do not bring into contact with bitumen. Use MARMOR + GRANIT SILICON for marble and natural stone.

**Work safety:** Not subject to labelling obligation in accordance with GHS.

GISCODE D1. Remove sealant with soap and water, do not allow to dry on the skin. If material gets into your eyes, flush thoroughly with water. Consult an eye specialist if necessary. The following applies with the antique white and silver-grey oak colours: Attention! Dangerous respirable droplets can occur when spraying. Do not inhale aerosol or mist. A data sheet can be downloaded from the Internet at [www.lugato.de](http://www.lugato.de).

**Disposal:** Allow residual contents to harden and dispose of as domestic waste / construction site waste. Recycle empty packaging.

## If you're not sure of something, please ask!

Feel free to give us a call. You can reach the LUGATO experts at: +49 (0)40 6 94 07-222.



Responsible Care (RC) for the chemical industry means taking responsible action. This is made clear through a worldwide initiative. In many countries, chemical associations run national RC programmes. Thousands of companies with millions of employees are active in the international initiative. The goal is voluntary commitment to do more than just the compulsory: Promoting sustainability, demonstrating product responsibility, creating more safety for factories and the neighbourhood, improving health protection at the workplace and improving environmental protection. Within the scope of its membership in the German Chemical Industry Association (Verband der deutschen chemischen Industrie), LUGATO has committed itself to adhere to this objective.

The statements made in this information sheet reflect our current knowledge and level of experience. Since we do not have influence on the object-specific circumstances and the correct execution of the work, we can only guarantee the consistent quality of our products. For that reason, in case of doubt, verify the suitability of the product through a sufficient number of test applications. A direct legal liability can be derived neither alone from the instructions in this information sheet nor from any verbal consultation. The publication of this technical information sheet invalidates all previous editions. Subject to change without prior notice.

EU: LUGATO GmbH & Co. KG, Großer Kamp 1,  
D-22885 Barsbüttel, ☎ +49 (0)40 69407-0  
Import /sales Schweiz: Puag AG, Oberebenestrasse 51,  
CH-5620 Bremgarten, CH-Infoline: 0848 810 800  
technik@lugato.de, Internet: www.lugato.de

Copyright by LUGATO. Stand 10/2024

**LUGATO**