

NEUER ANSTRICH FÜR GARAGEN + BALKONE



Creates highly durable and resistant surfaces.

Product performance

- | Top quality 1-component acrylic coating.
- | For highly durable and resistant surfaces.
- | Very easy application. Excellent adhesion.
- | Decorative and silk matt.
- | Can be driven over and walked on. Robust. Tyre-proof.
- | Fast drying. High covering capacity.
- | Creates easy-to-clean surfaces.
- | Oil and weather resistant.
- | Indoor and outdoor use.

Applications

For sealing balconies, terraces, outside stairs, single garages.



NEUER ANSTRICH on a balcony: Decorative. Satin matt. Fast drying. Abrasion resistant. Robust.

Substrates and preparation

Suitable substrates	Concrete, cement screeds (min. 28 days old).
Characteristics	Load bearing, clean, dry, dust, grease and oil free. Free from tyre abrasion, binder skin and smoothed surface.
Preparation	Mechanically roughen surfaces with a smooth coat, e.g. by milling.

Processing

Stir product thoroughly. Apply NEUER ANSTRICH FÜR GARAGEN + BALKONE undiluted twice with a solvent-resistant paint roller or brush. The first coat must dry for at least 4 hours before applying the second one. Clean tools immediately after use with all-purpose thinner. Comply with the information in the hazardous material box.

Product data

Quantity required	Approx. 100 ml/m ² per coating. Determine the exact application values through test coating.
Yield (2.5l)	Approx. 12.5 m ² (two coats).
Processing temperature	10–25 °C.
Load capacity	Dust-dry after about 1 hour, recoatable after about 4 hours, vehicles can be driven on it after 7 days at the earliest.
Colour/gloss degree	Cement grey/semi-matt.
Ingredients	Acrylic resin, pigments, fillers, solvents, additives.
Pack sizes	2.5l.
Shelf life	In original packaging min. usable until: see label. Store dry, closed, cool and frost-free.

Please consider

For garage floors, a test area should be coated beforehand and the adhesion at the tyre contact points should be checked. Low temperatures and high humidity extend the drying time.

Health & safety:



Contains: Hydrocarbons, C9, aromatics, 1-methoxy-2-propanol, xylene. Flammable liquid and vapour. Can irritate the respiratory system. May cause drowsiness and dizziness. Harmful to aquatic life with long lasting effects. Attention! Spraying may produce dangerous respirable droplets. Do not inhale aerosol or mist. If medical advice is necessary, keep the packaging or marking label ready. Keep out of the reach of children. Keep away from hot surfaces, sparks, open flames as well as other ignition sources. Do not smoke. Only use outdoors or in well-ventilated rooms. In case of fire: Use water jet, extinguishing powder, foam or CO₂ for extinguishing. Dispose of contents/container according to local and national regulations.

UFI: 82AW-QP3D-JGOA-UDYA



Attention

Disposal:

Allow residual content to harden and dispose as domestic or construction site waste. Recycle packaging free from residues. Directive: 2004 / 42 / EG / II A / i (600/500): < 500 g/l VOC.

If you're not sure of something, please ask!

Feel free to give us a call. You can reach the LUGATO experts at: +49 (0)40 6 94 07-222.



Responsible Care (RC) for the chemical industry means taking responsible action. This is made clear through a worldwide initiative. In many countries, chemical associations run national RC programmes. Thousands of companies with millions of employees are active in the international initiative. The goal is voluntary commitment to do more than just the compulsory: Promoting sustainability, demonstrating product responsibility, creating more safety for factories and the neighbourhood, improving health protection at the workplace and improving environmental protection. Within the scope of its membership in the German Chemical Industry Association (Verband der deutschen chemischen Industrie), LUGATO has committed itself to adhere to this objective.

The statements made in this information sheet reflect our current knowledge and level of experience. Since we do not have influence on the object-specific circumstances and the correct execution of the work, we can only guarantee the consistent quality of our products.

For that reason, in case of doubt, verify the suitability of the product through a sufficient number of test applications. A direct legal liability can be derived neither alone from the instructions in this information sheet nor from any verbal consultation.

The publication of this technical information sheet invalidates all previous editions. Subject to change without prior notice.

EU: LUGATO GmbH & Co. KG, Großer Kamp 1,
D-22885 Barsbüttel, ☎ +49 (0)40 69407-0
Import/sales Schweiz: Puag AG, Oberebenestrasse 51,
CH-5620 Bremgarten, CH-Infoline: 0848 810 800

Copyright by LUGATO. Stand 11/2020

LUGATO